

# Technical Data Sheet

## StoLook Wax

Transparent protective wax



### Characteristics

<b>Area of application</b>	<ul style="list-style-type: none"> <li>interior</li> <li>as a protective coating for StoCalce Marmorino, StoCalce Veneziano, and StoCalce Fondo surfaces</li> <li>as finishing coat in combination with StoLook Effect Powder</li> <li>do not use in splash zones</li> </ul>
----------------------------	--

<b>Properties</b>	<ul style="list-style-type: none"> <li>protects the surface</li> <li>resistant to mechanical stress</li> <li>provides protection against early soiling</li> </ul>
-------------------	---

<b>Appearance</b>	<ul style="list-style-type: none"> <li>enhances the gloss and depth effect</li> </ul>
-------------------	---

### Substrate

<b>Requirements</b>	The substrate must be firm, dry, clean, and load-bearing.
---------------------	---

### Application

<b>Application temperature</b>	Lowest temperature of substrate and air: +5 °C
--------------------------------	--

Consumption	Type of application	Approx. consumption	
	per application cycle	0.05	l/m <sup>2</sup>
Material consumption depends on the application, substrate, and consistency, among other factors. The stated consumption values are only to be used as a guide. If required, determine precise consumption values on the basis of the specific project.			

<b>Application</b>	apply a thin and uniform wax layer and polish it using a cloth or a non-abrasive spatula
--------------------	--

<b>Drying, curing, ready for next coat</b>	Only apply wax protective coatings after approx. 4-8 days of drying time. Drying time depends on the surface technique employed. Applying the wax too early can lead to discolouration.
--	---

# Technical Data Sheet

## StoLook Wax

**Cleaning the tools** Clean tools with water immediately after use.

**Notes, recommendations, special information, miscellaneous** Excessive amounts of wax or non-uniform application can lead to whitening and fogging.  
The waxed surface can be cleaned with a damp cloth or commercially-available soap or washing-up liquid. Do not use aggressive cleaning agents, e.g. scouring cream, descalers, and sharp-edged cleaning tools.  
When reworking waxed surfaces, make sure to remove the wax layer before applying a new layer.

### Delivery

**Colour shade** milky white, tintable with StoTint Aqua

**Packaging** tin

### Storage

**Storage conditions** Store tightly sealed in frost-free conditions.

**Storage life** The quality of the product in its original container is guaranteed until the maximum storage life has expired. The storage life information is included in the batch number on the container.  
Explanation of batch no.:  
digit 1 = last digit of the year, digits 2 + 3 = calendar week  
Example: 1450013223 - storage life ends week 45 in 2021

### Identification

**Product group** Wax

**Safety** Observe the Safety Data Sheet!

### Special notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.  
Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on the Internet.

## Technical Data Sheet

---

### **StoLook Wax**

Sto SE & Co. KGaA  
Ehrenbachstr. 1  
79780 Stühlingen / Germany  
Phone: +49 7744 57-0  
Fax: +49 7744 57-2178  
[Infoservice.export@sto.com](mailto:Infoservice.export@sto.com)  
[www.sto.com](http://www.sto.com)